



Hints from the Model Garage





RUBBER BALL




To weatherproof a trailer hitch while it's not in use, all you need is an old rubber ball and a plastic vegetable bag. Slit the ball enough to slip it over the metal ball of the hitch. Use a rubber band to hold the plastic bag in place.



Sudden stops harm new brakes. A new car or one with newly relined brakes should be broken in gently until the linings become burnished. Rough use during a break-in period often causes abnormal wear and may cause uneven brake action.




Erasing rust spots is neater and easier than sanding them off. The eraser can be a long pink one made for electric erasing machines or a wood-covered type used by typists. Chuck the eraser in an electric drill, letting $\frac{1}{4}$ " stick out.



Pipe-smoking drivers can keep a full set of pipes at hand by fastening a simple rack to the sun visor. It's made of perforated hardboard and has wire tool holders to slip the pipes in. Rubber bands are cut from an inner tube.


More Hints from the Model Garage




A grease-gun extension of standard pipe ($\frac{3}{8}$ " fits most guns) will reach once-inaccessible fittings. About $1\frac{1}{2}$ ' long, it lets you pump the handle freely, away from grime. The grease gun can be pressed firmly because the extension is rigid.



With a shoe scraper always handy, mud and slush needn't dirty up the inside of a car. This swing-in, swing-out blade bolts to the car frame, and because it's spring-loaded stays put except when pushed sideways by the user's foot.



Installing a wire hose clamp in tight quarters needn't be a knuckle-buster. Before slipping the clamp on the hose, expand it until the ends touch and slip a small washer over them. When the hose is in place, pull off the washer.



A bump strip keeps concrete block from scratching a car's paint job when the door is opened inside the garage. A 3' length of Celotex, 6" to 12" wide, makes a soft yet durable cushion. Masonry or steel cut nails at both ends hold it.