

## **1. CORNSTARCH PUTS A SHINE** on a car with a minimum of elbow grease. Try sprinkling a little on after you have applied the polishing wax and before you do the rubbing. You'll find that the task of producing a durable luster is considerably simplified. The cornstarch comes off with the rag, which should be shaken out often during the rubbing.–R. H. E.

**2.** LOOSE FENDER BEADING may be anchored in place with narrow strips of aluminum bent over the beading and under the fender and body, as shown in the drawing. This is a good way of retaining beading that threatens to come off because of rotted fabric or damage to the fender or body.-W.E.L.


**3. GAS-LINE RATTLES** sometimes occur when the pipe joggles against frame members through which it passes. An easy remedy is to use rubber corks, drilled, split, and inserted as shown. They will not only stop rattles but will also prevent vibration and possible failure of the line.—A. H. W.


**4. TIGHT CABLE LUGS** can be pulled off without straining battery posts by means of this simple puller. The notch in the length of channel stock goes around the post and under the terminal. A thumbscrew or a bolt and wrench will serve.—A. H. W.

**5. THEFT OF ACCESSORIES** can be made difficult with this homemade lock nut. Few thieves will have a wrench for the hollow-head setscrew that locks the nut. The setscrew should be flush and should engage a dimple drilled in the stud.-T. K.









Drawings by STEWART ROUSE

